

GENERAL

You don't need special tools to install this fixture. Be sure to follow the steps in the order given. **NOTE: Proper wiring is essential for the safe operation of this fixture. Read the instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician.**

WARNING

BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF. EITHER THE FUSE REMOVED OR THE CIRCUIT BREAKER OFF.

INSTALLATION

IMPORTANT: DO NOT ATTACH FIXTURE DIRECTLY TO OUTLET BOX.

1. Power feed to reflector assembly from left side. See Fig. 1.
2. Drill 1/2 inch diameter or notch hole in surfaces where cable will be running through shelving. See Fig. 2.

3. Secure reflector assembly directly to showcase using the mounting screws provided. See Fig. 3.
4. Run cable, covered with sleeving, through predrilled holes directly to transformer. **NOTE: DO NOT NAIL OR SCREW THROUGH CABLE TO ATTACH TO A SURFACE.**
5. Mount transformer as close as possible to the lighting system on a vertical surface. Transformer may be installed horizontally if all the following criteria are met:
 - Load below 80% of max. load
 - No insulation must surround transformer
 - Ambient temperature must be below 130°F
 Refer to instruction sheet A-716L for transformer installation (included with transformer).
6. Space lampholders no closer than 11 inches center to center.
7. Mount lampholder a minimum of 1 inch from closed end of all surfaces or partitions.

