

IMPORTANT SAFETY INSTRUCTIONS

Lighted lamp is HOT!

TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS:

- Be sure the electricity to the system you are working on is turned off; either the fuse removed or the circuit breaker set at off.
- Turn off/unplug and allow to cool before replacing lamp.
- Lamp gets HOT quickly! Contact only switch/plug when turning on.
- Do not touch hot lens, guard, or housing.
- Keep lamp away from materials that may burn.
- Do not touch the lamp at any time. Use a soft cloth. Oil from skin may damage lamp.
- Use of other manufacturers' components will void warranty, listing and create a potential safety hazard.
- Caution—risk of shock. 24v system not suitable for outdoor use.
- Do not install within 10' (3m) of a pool, spa, or fountain.
- Dimming halogen lamp may reduce the lamp life.
- Save these instructions.

ASSEMBLY

- 1) Remove the screws (A) that secure the end cap (B) to the fixture housing (C).
- 2) Slide glass lens (D) out of fixture housing (C).
- 3) Install lamp.
- 4) Slide optional 9355-12 eggcrate honey comb louver (not included) to provide 45° glare cut-off.
- 5) Slide glass lens (D) into fixture housing (C).
- 6) Place end cap (B) onto fixture housing (C). Secure with screws (A).

GROUND MOUNTING

- 1) Slip fixture cable through 9344 stake (not included) and thread stake into swivel base.
- 2) Press stake into hole in ground and tamp to secure in place.
- 3) Attach fixture cable to main supply cable with silicone wire nuts or other wet listed connector (not included).
- 4) Loosen swivel screw (E) and adjust to desired position; retighten swivel screw (E).

WALL / DECK MOUNTING

- 1) Drill hole in surface for wire (or) break away tab on swivel base for surface mount wire.
- 2) Attach to surface through holes on swivel base with screws (not included) (FIG. 2).
- 3) Attach fixture cable to main supply cable with silicone wire nuts or other listed connector (not included).
- 4) Loosen swivel screw (E) and adjust to desired position; retighten swivel screw (E).

NOTE: LENS RETAINING RING IS USED FOR OPTIONAL LOUVERS OR GLASS ACCESSORIES

