





VANDEVENTER LED WALL/BATH SCONCE

4122991S

General Product Information



Suggested/Required Tools



Safety Information

CAUTION-RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.


USE MINIMUM 90°C SUPPLY CONDUCTORS.



Turn off electrical current at the source before working with any lighting fixture or portable lamp.

Install and use this product in adherence with local electrical codes and regulations.





INSTRUCTIONS

I. Preparing the Fixture

1. Secure the mounting plate to the electrical box with two mounting plate screws.

II. Wiring the Fixture

1. Safety first! Locate the circuit breaker and switch it off to cut off the power supply to the relevant circuits to ensure there's no electricity running through the wiring.
2. Connect the LED driver input wires to the local power line wires. Twist the bare ends of the following pairs of wires together using a wire nut to secure a connection:
 - a) Neutral driver wire (white) to neutral power line wire
 - b) Hot driver wire (black) to hot power line wire
3. Ensuring the driver output wires are accessible, secure the mounting bar to the junction box using the mounting screws.
4. In accordance with local electrical codes, connect the fixture ground wire (bare copper or silver wire) to suitable ground. This may be a green ground screw on the mounting plate, which the ground wire should be tightly wrapped around or a house wire (green or bare copper wire without insulation).
5. Now, twist the bare ends of the following pairs of wires together using a wire nut to secure a connection:
 - a) Black (negative) driver wire (output) to (negative) fixture wire
 - b) Red (positive) driver wire (output) to (positive) fixture wire
6. Carefully tuck all the wires and the driver behind the mounting plate into the junction box.

III. Installing the Fixture

1. Mount the fixture base onto the mounting plate studs and secure it with the two cap nuts.
2. Place the shade in between the fixture brackets and secure it in place by screwing the finials to the brackets.