

ARILDA PENDANT

6537001

General Product Information:




Tool Needed: Phillips-Head Screwdriver, and provided Allen Screwdriver

CAUTION-RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

USE MINIMUM 90°C SUPPLY CONDUCTORS.

SAVE THESE INSTRUCTIONS!



Instructions

1. Determine the wanted height or look of the fixture with the provided swivel, stems, and chain and assemble them by screwing them together. All parts may be used alone or in combination.
2. Feed the fixture wires through the stems/chain and screw the stem assembly to the top of the pendant.
3. Unscrew the collar nut off the screw collar and place it onto the stem/chain followed by the canopy.
4. Screw the screw collar onto the threaded nipple.
5. Feed the fixture wires through the threaded nipple and screw the mounting plate assembly onto the stem/chain assembly.
6. Align and secure the mounting plate to the junction box.
7. Connect the fixture to a suitable ground in accordance to local electrical codes.
8. Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
9. Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
10. Neatly place all the wires into the junction box, place the canopy onto the ceiling, and secure it in place by screwing the collar nut tightly onto the screw collar.
11. Screw the lamp into the socket. Refer to the label on the socket for Max Wattage Information.